

MERICRUSHER

MJ-1.4 ST

For versatile crushing



MERICRUSHER

MERICRUSHER

MJ-1.4 ST

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of farm land
- Reclaiming soil for farming
- Farm road maintenance
- Orchard clearing

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting
- Clearing of power lines
- Clearing of firebreaks

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame)
- STD or STE Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented) or FT-44 safety clutch
- Possibility to turn the direction of the rotor

OPTIONS

- Push bar (hydraulic)
- Rear roller (hydraulic)
- Guide plate (front fixed)
- Hydraulic Top Link

Base machine demand

Tractor

Mounting

CAT-1

Auxiliary hydraulic

2 pcs. double acting

PTO

(540) / 1000 rpm

Working speed

Creeper gear recommended

Technical data:

Power range

50-90 hp

Transmission

Mechanical PTO

Final transmission

Chain 2-row

Clutch

POC-2 or FT44

Rotor diameter / width

400 / 1350mm

16 / 53 inch

Cutter qty.

60 (T25 Rotor)

Working depth

200 mm / 8 inch

Main dimensions:

Length

1550 mm

61 inch

Width

1800 mm

71 inch

Height

1010 mm

40 inch

Weight

710 kg

1570 lbs

Weight, with options

1050 kg

2320 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com