

MERICRUSHER

MJ-2.3 ST / DT

For versatile crushing



MERICRUSHER

MERICRUSHER

MJ-2.3 ST / DT

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of farm land
- Reclaiming soil for farming
- Farm road maintenance
- Orchard clearing

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting
- Clearing of power lines
- Clearing of firebreaks

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame)
- STD or STE Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented) or FT-44 safety clutch
- Possibility to turn the direction of the rotor

OPTIONS

- Push bar (hydraulic)
- Rear roller (hydraulic)
- Guide plate (front fixed)
- Hydraulic Top Link

Base machine demand

Tractor

Mounting

CAT-2

Auxiliary hydraulic

3 pcs. double acting

PTO

(540) / 1000 rpm

Working speed

Creep gear recommended

Technical data:

Power range ST /DT

70-90 hp

90-150 hp

Transmission

Mechanical PTO

Final transmission

Chain 2-row

Clutch

POC-2 or FT44

Rotor diameter / width

400 / 2250mm

16 / 89 inch

Cutter qty.

96 (T25 Rotor)

Working depth

200 mm / 8 inch

Main dimensions:

Length

1550 mm

61 inch

Width

2700 mm

106 inch

Height

1220 mm

48 inch

Weight ST / DT

1080 / 1230 kg

2380 / 2710 lbs

Weight, with options
ST / DT

1580 / 1730 kg

3480 / 3810 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com