

MERICRUSHER

MJH-1.2 STG/DTG

For versatile crushing



MERICRUSHER

MERICRUSHER

MJH-1.2 STG/DTG

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST / ORCHARD

- Crushing of stumps and roots
- Crushing of planting rows
- Soil preparing for planting

EQUIPMENT

FEATURES

- Welded fixed counter blades
- Welded hardox– liner in frame
- UNTH Rotor with cost effective carbide cutters multiple cutter options available
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

OPTIONS

- Guide plate (hydraulic front/rear)
- Support skids
- Rear roller

Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	2-3 pcs. double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range STG / DTG	100—250 / 200-300 hp
Transmission	Mechanical PTO
Final transmission	Gear (G-serie)
Clutch	POC-3
Rotor diameter / width	600 / 1110 mm
Cutter qty. base + sides	44+12
Working depth	300 mm

Main dimensions:

Length	2300 mm
Width	1520 mm
Height	1520 mm
Weight STG / DTG	1150 / 1400kg
Weight, with options STG / DTG	1600 / 1900 kg



SUOKONE OY
Lastaajantie 1
88610 Vuokatti

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com