

MERICRUSHER

MJHS-241 STX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJHS-241 STX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT, UNTH or STB Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Rotating sizing screen (hydraulic front/rear)
- Door type sizing screen (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link

Base machine demand

Tractor

Mounting

CAT-3

Auxiliary hydraulic

3 pcs. double acting

PTO

1000 rpm

Working speed

Creeper gear recommended

Technical data:

Power range

200 - 400 hp

Transmission

Mechanical PTO

Final transmission

Gear (X-serie)

Clutch

POC-3 XL

Rotor diameter / width

600 / 2410mm

24 / 95 inch

Cutter qty.

110 (T25 STB Rotor)

Working depth

300 mm / 12 inch

Main dimensions:

Length

2540 mm

100 inch

Width

2910 mm

115 inch

Height

1430 mm

57 inch

Weight

2500 kg

5500 lbs

Weight, with options

3700 kg

8160 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com