

MERICRUSHER

MJS-2.0 / 2.5 DT

For versatile crushing



MERICRUSHER

MERICRUSHER

MJS-2.0 / 2.5 DT

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame)
- STD / UNT Rotor with cost effective carbide cutters
- Possibility to turn the direction of the rotor.

OPTIONS

- POC - Pressure operated safety clutch (SUOKONE patented)
- Push bar (hydraulic)
- Rear roller (hydraulic)
- Guide plate (front fixed)
- Hydraulic Top Link

Base machine demand

Tractor	
Mounting	CAT-2
Auxiliary hydraulic	3 pcs. double acting
PTO	(540) / 1000 rpm
Working speed	Creep gear recommended

Technical data:

Power range	110 - 180 hp	120 - 180 hp
Transmission	Mechanical PTO	
Final transmission	Chain 3-row	
Clutch	POC-2 or FT44	
Rotor diameter 2.0 / 2.5	500 mm	20 inch
Rotor width 2.0 / 2.5	1940 / 2440 mm	76 / 96 inch
Cutter qty. 2.0 / 2.5	86 / 110 (T25 Rotor)	
Working depth	250 mm / 10 inch	

Main dimensions:

Length	1580 mm	62 inch
Width 2.0 / 2.5	2410 / 2910 mm	95 / 115 inch
Height	1380 mm	54 inch
Weight 2.0 / 2.5	1400 / 1520 kg	3090 / 3350 lbs
Weight, with options 2.0 / 2.5	1860 / 2030 kg	4100 / 4480 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com