

MERICRUSHER
MJS-243 STG / DTG

For versatile crushing



MERICRUSHER

MERICRUSHER

MJS-243 STG / DTG

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolted adjustable counter blades
- Hardox liner in frame (bolted)
- UNT Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor.
- Bolted lift arm brackets

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Guide plate hydraulic (front)
- Rear roller hydraulic (short arms)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

Technical data:

Power range STG / DTG	120 - 240 hp	150 - 300 hp
Transmission	Mechanical PTO	
Final transmission	Gear (G-serie)	
Clutch	POC-3	
Rotor diameter / width	500 / 2408mm	20 / 95 inch
Cutter qty. base + sides	102 + 12 (UNT Rotor)	
Working depth	250-300 mm / 10-12 inch	

Main dimensions:

Length	1650 mm	65 inch
Width STG / DTG	2815 / 2835 mm	112 / 113 inch
Height	1360 mm	54 inch
Weight STG / DTG	1650 / 1890 kg	3640 / 4170 lbs
Weight, with options STG / DTG	2250 / 2500 kg	4960 / 5500 lbs



SUOKONE OY
Lastaajantie 1
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com